

MODEL 5230K30CS

**5 HP TWO-STAGE, TWO-CYLINDER
PORTABLE ELECTRIC COMPRESSOR**



ROLAIR® STANDARD FEATURES

PUMP: Two Stage, Enbloc Cast-Iron Cylinders, Ball Bearings, Splash Lubricated, Automotive-Style Bearing Inserts on Connecting Rods, High-Efficiency Reed Valves, Oil Sight Gauge, Low RPM to Ensure Long Life and Trouble-Free Performance.

MOTOR: 5 HP 1740 RPM Open Drip-Proof
230 Volts, 60 Hz Ball Bearings
Overload Protected with Manual Reset
S-1 Rated for Continuous Duty

PERFORMANCE @ 90 PSI:

Cu. Ft. Displaced - 23.1
Cu. Ft. Delivered - 18.8

TANK ASSEMBLY: Non-Code, 9 Gallons

DIMENSIONS:

L46" x W27" x H34"

WHEELS: Two 410/350 x 4
2-Ply Fully-Pneumatic with Sealant

APPROXIMATE SHIPPING WEIGHT:
296 lb.

STANDARD EQUIPMENT

- Constant-Speed with Pilot Unloader
- Universal Quick-Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- Accessory Support Bracket
- Pressure Gauge 0-300 in 5 lb. Graduations
- 120/150 PSI Operating Pressure
- Safety Relief Valve
- Air-Cooled Intercooler

OPTIONAL EQUIPMENT

20-Gallon ASME Receiver, Filter-Regulator-Lubricator Sets