

BESSEY® shop floor clamps

For Welding and Fabricating



Simply better.

A solid and dependable performer day-in and day-out on your shop floor

- 1** Enhanced clamp force and high stability. Patented rail profile offers more clamp force with fewer spindle turns. (For 660 & 1200)
- 2** Standard swivel pads are field replaceable. (For 660 & 1200)
- 3** Heat treated, high carbon Acme threaded screw – tempered and quenched to give greater loading capacity and longer service life.
- 4** High-strength electro-galvanized sliding pin T-handle – rounded ends for comfort, size engineered to load capacity. Ergonomic grip is available as an accessory.
- 5** New U-Shaped tempered steel sliding arm offers straight-line power transmission. Great stability. (For 660 & 1200)



660 & 1200

Catalog #	Throat Depth	Clamping Capacity	Clamping Force
Light duty (MMS)			
MMS-4	2-1/4"	4"	400 lbs
MMS-8	2-1/4"	8"	400 lbs
MMS-12	2-1/4"	12"	400 lbs
Light duty (660-S, 1200-S)			
660-S8	4"	8"	726 lbs
660-S12	4"	12"	726 lbs
660-S18	4"	18"	726 lbs
1200-S8	4-3/4"	8"	1320 lbs
1200-S12	5-1/2"	12"	1320 lbs
1200-S18	4-3/4"	18"	1320 lbs
1200-S24	4-3/4"	24"	1320 lbs
Heavy duty (STB)			
STB-12	7"	12"	4880 lbs
STB-18	7"	18"	4880 lbs
STB-24	7"	24"	4880 lbs
STB-36	7"	36"	4880 lbs

With BESSEY® MorPad

Catalog #	Throat Depth	Clamping Capacity	Clamping Force
Medium duty (SGL)			
SGL-8	4-3/4"	8"	1800 lbs
SGL-12	4-3/4"	12"	1800 lbs
SGL-18	4-3/4"	18"	1800 lbs
SGL-24	4-3/4"	24"	1800 lbs
Regular duty (SQ)			
SQ-4*	4-3/4"	6"	1330 lbs
SQ-8	5-1/2"	8"	2660 lbs
SQ-12	5-1/2"	12"	2660 lbs
SQ-16	5-1/2"	16"	2660 lbs
SQ-20	5-1/2"	20"	2660 lbs
SQ-24	5-1/2"	24"	2660 lbs
SQ-36	5-1/2"	36"	2660 lbs
SQ-48	5-1/2"	48"	2660 lbs
SQ-60	5-1/2"	60"	2660 lbs

*SQ-4 comes with standard pad.



<http://www.facebook.com/BesseyToolsNorthAmerica>



<http://www.youtube.com/user/BesseyTools>



<http://www.besseytools.com/>

E-NEWSLETTER - Email us at info@besseytools.com to request sign-up

03-2011-v1-E