

3PT Hitch Log Splitter



3PT22T25

PRODUCT DESCRIPTION	COMMERCIAL GRADE 3PT HITCH HORIZONTAL/VERTICAL LOG SPLITTER 22 TON
BRAND	BOSS INDUSTRIAL
MODEL NO.	3PT22T25
UPC	853676004212
TECHNICAL SPECIFICATIONS	
TRACTOR REQUIREMENT	CATEGORY 1 OR CATEGORY 2
SPLITTING FORCE	MAX. 22 TON, TRACTOR PSI DEPENDANT
TRACTOR HYDRAULIC PRESSURE RECOMMENDED	2000 - 4000 PSI
TRACTOR HYDRAULIC FLOW RECOMMENDED	8~12 GPM
SPLITTING CYCLE	THE FASTED 11 SECONDS, TRACTOR GPM DEPENDANT
MAX. SPLITTING LENGTH	25 IN.
SPLITTING WEDGE HEIGHT	8 IN.
CYLINDER BORE	4.0 IN.
OPERATION MODE	ONE HAND OPERATION
AUTO RETURN	YES
WARRANTY	2 YEAR INCL. HYDRAULICS

PACKING INFORMATION	
PACKING METHOD	CARDBOARD BOX W/ METAL CRATE
PACKING DIMENSIONS	74" (L) x 26" (W) x 26" (H)
G.W. / N.W.	565 / 442 LBS
LOADING QUANTITY	71 PCS PER 40' HC

3PT Hitch Log Splitter

WHY BOSS

Boss Industrial commercial grade 3PT Hitch 22 Ton horizontal/ vertical log splitter WINS with these unique features:

- Commercial grade hydraulic system, allows this unit match wide range of tractors' needs for hydraulic flow and pressure rated from low to high.
- Easy to assemble. Only 2 sets of hardware to bolt the assemblies together
Packing list:
 - 1) Beam/ 3PT Frame Top Assembly x 1
 - 2) 3PT Frame Leg x 4
 - 3) 3PT U-shape mounting bracket x 1
- Rugged steel full beam and special tool alloy steel wedge for a lifetime of use
- Two extra large log trays included
- Patented mechanical pressure release system on hydraulic valve, improves valve performance and safety, eliminating the typical malfunctions and leaking of a traditional detent hydraulic valve
- 1/2" *100" inlet and outlet hydraulic hoses included
- Sturdy 3PT frame design provides extra stability