



STAINLESS STEEL SUMP PUMPS

APPLICATIONS

Ideal for average to high-volume water removal in residential spaces such as basements and crawl spaces.

FEATURES & BENEFITS

- A standard 300-grade stainless steel motor housing provides added corrosion protection for maximum pump life
- An energy-efficient PSC motor draws fewer amps to reduce electricity costs
- Contractor-preferred snap-action float switch for reliable automatic operation
- An elevated suction design provides superior clog-resistance



Model	Item No.	UPC	HP	Volts	Amps	Watts	Cord Length	Discharge	Gallons Per Hour at Height					Shut-Off	On/Off Levels	Minimum Basin Diameter
									5'	10'	15'	20'	25'			
RL33CSS	14942793	0 10121 00165 7	1/3	115	3.5	400	10'	1-1/2" FNPT	3500	2800	2000	500	-	23'	On: 9"-11" Off: 3"-5"	18"
RL50CSS	14942794	0 10121 00166 4	1/2	115	4	450	10'	1-1/2" FNPT	3900	3150	2250	1500	-	25'	On: 9"-11" Off: 3"-5"	18"
RL75CSS	14942795	0 10121 00167 1	3/4	115	5.5	650	10'	1-1/2" FNPT	4500	4000	3200	2500	1500	30'	On: 9"-11" Off: 3"-5"	18"

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL33CSS	11.4"	8.5"	14.6	21.5	0.82	48	16	3
RL50CSS	11.4"	8.5"	14.6	21.6	0.82	48	16	3
RL75CSS	11.4"	8.5"	14.6	23.3	0.82	48	16	3

Stainless Steel Sump Pumps

