



ROLAIR® STANDARD FEATURES

PUMP: Single Stage, Three Cast-Iron Cylinders, Aluminum Heads for Faster Heat Dissipation, Ball Bearings, Splash Lubricated, High-Efficiency Reed Valves, Oil Sight Gauge and Trouble-Free Performance. **For Pump Specifications See Reverse Side**

TANK : 60 Gallon - ASME

APPROXIMATE SHIPPING WEIGHT:
298 lb.

MOTOR: Open Drip-Proof
220 Volt – 60 Hz – 3450 RPM - 1 Phase
S-1 Rated for Continuous Duty

16 CFM Delivered @ 100 PSI

CSA Approved

STANDARD EQUIPMENT

- Pressure Switch - Start/Stop Operation 110-135 PSI Settings, On/Off Switch
- Automatic Unloading Device for Loadless Starts
- Heavy-Duty Shut-Off Valve
- Pressure Gauge - 0-200 PSI in 5 lb. Graduations
- Safety Relief Valve - ASME Approved
- V-Belt Drive
- Intake Filter/Silencer with Replaceable Element
- Totally-Enclosed Steel Belt Guard

MODEL PMP13PT03A



SPECIFICATIONS

NO. OF CYLINDERS	CYLINDERS BORE & STROKE (inches)	OIL CAPACITY (oz.)	FWHL DIAMETER (inches)	DRY WEIGHT (lb.)	MAXIMUM PRESSURE
3	2.56 x 2.56 x 1.89	24	10.5	63	150 PSI

PERFORMANCE

HP	DISCHARGE PRESSURE	CFM DISPLACED	CFM DELIVERED @ 100 PSI	PUMP RPM
5	100 PSI	22	16	1200