



FIBER CEMENT



ANTI-FRICTION COATING
Resists Corrosion and Gumming



POLYCRYSTALLINE DIAMOND TEETH
Extends Cutting Life in Fiber Cement



LASER CUT TECHNOLOGY
Reduces Wobble and Warping



FIBER CEMENT CUTTING CIRCULAR SAW BLADES

	Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (in)	Arbor Size	Part No.
FIBER CEMENT	7-1/4"	4T	Fiber Cement	10°	0.071"	5/8", ◆	48-40-7000
	10"	6T	Fiber Cement	10°	0.079"	5/8"	48-40-7010
	12"	8T	Fiber Cement	10°	0.087"	1"	48-40-7020

BASIC FRAMING

ANTI-KICKBACK SHOULDER
Prevents Binding

PRECISION GROUND TEETH
Stays Sharper, Longer

EXPANSION SLOTS
Reduced Blade Stress For Accurate Cuts



BASIC FRAMING CIRCULAR SAW BLADES

	Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (in)	Arbor Size	Quantity	Part No.
FRAMING	7-1/4"	24	Framing	20°	0.063"	5/8", ◆	10	48-41-0710
	7-1/4"	24	Framing	20°	0.063"	◆	10	48-41-0713



Nothing but **HEAVY DUTY.**

CIRCULAR SAW
BLADES



METAL | WOOD | FIBER CEMENT



**CUTS
COOLER**

**INCREASED
ACCURACY**

**LONGER
LIFE**



NEW

METAL CUTTING



LASER CUT TECHNOLOGY
Reduces Wobble and Warping



COBALT INFUSED TUNGSTEN CARBIDE
Extends Cutting Life and Maintains Tip Sharpness



CUTS COOLER
No Extreme Heat Build-up



WOOD CUTTING



ANTI-FRICTION COATING
Resists Corrosion and Gumming



LASER CUT TECHNOLOGY
Reduces Wobble and Warping



COBALT INFUSED TUNGSTEN CARBIDE
Extends Cutting Life and Maintains Tip Sharpness



METAL CUTTING CIRCULAR SAW BLADES

	Diameter	No. of Teeth	Application	Thickness	Hook Angle	Kerf Thickness (in)	Arbor Size	Part No.
METAL & STAINLESS	5-3/8"	30	Metal & Stainless	1/16" - 3/16"	0°	0.063"	20 mm	48-40-4070
	5-3/8"	30	Metal & Stainless	1/16" - 3/16"	0°	0.063"	5/8"	48-40-4205
	8"	42	Metal & Stainless	1/16" - 1/2"	0°	0.073"	5/8"	48-40-4515
	8"	50	Thin Metal & Stainless	up to 3/32"	0°	0.073"	5/8"	48-40-4520
	14"	72	Metal & Stainless	1/16" - 3/16"	0°	0.087"	1"	48-40-4505
METAL	5-7/8"	34	Metal	1/16" - 3/16"	2°	0.063"	20 mm	48-40-4215
	6-1/2"	48	Metal	1/16" - 3/16"	2°	0.063"	5/8"	48-40-4220
	6-7/8"	36	Metal	1/16" - 3/16"	2°	0.063"	20 mm	48-40-4225
	7"	40	Metal	1/16" - 3/16"	2°	0.071"	20 mm	48-40-4230
	7-1/4"	48	Metal	1/16" - 3/16"	2°	0.071"	5/8"	48-40-4235
	7-1/4"	48	Metal	1/16" - 3/16"	2°	0.071"	20 mm	48-40-4237
	7-1/4"	70	Thin Metal	up to 3/32"	-5°	0.071"	5/8"	48-40-4240
	9"	48	Metal	1/16" - 3/16"	0°	0.071"	1"	48-40-4255
	10"	50	Metal	1/16" - 3/16"	0°	0.079"	5/8"	48-40-4260
	12"	60	Metal	1/16" - 3/16"	0°	0.087"	1"	48-40-4265
ALUMINUM	14"	90	Thin Metal	up to 3/32"	10°	0.087"	1"	48-40-4510
	5-3/8"	50	Aluminum	1/16" - 1/4"	-5°	0.063"	20 mm	48-40-4075
	5-7/8"	50	Aluminum	1/16" - 1/4"	-5°	0.071"	20 mm	48-40-4315
	6-1/2"	54	Aluminum	1/16" - 1/4"	-5°	0.071"	5/8"	48-40-4320
	7"	54	Aluminum	1/16" - 1/4"	-5°	0.079"	20 mm	48-40-4330
	7-1/4"	56	Aluminum	1/16" - 1/4"	-6°	0.079"	5/8"	48-40-4335
	8"	58	Aluminum	1/16" - 1/4"	-6°	0.094"	5/8"	48-40-4345
	9"	72	Aluminum	1/16" - 1/4"	-6°	0.094"	1"	48-40-4355
	10"	72	Aluminum	1/16" - 1/4"	-6°	0.110"	5/8"	48-40-4360
	12"	80	Aluminum	1/16" - 1/4"	-6°	0.118"	1"	48-40-4365
	14"	80	Aluminum	1/16" - 1/4"	-6°	0.126"	1"	48-40-4370

CERMET CARBIDE

WOOD CUTTING CIRCULAR SAW BLADES

	Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (in)	Arbor Size	Quantity	Part No.
FRAMING	5-3/8"	16	Framing	15°	0.063"	10 mm	1	48-40-0522
	5-1/2"	18	Framing	18°	0.063"	10 mm	1	48-40-0520
	6-1/2"	24	Framing	18°	0.063"	5/8", ◆	1	48-40-0620
	7-1/4"	24	Framing	18°	0.063"	5/8", ◆	1	48-40-0720
	8-1/4"	24	Framing	18°	0.083"	5/8", ◆	1	48-40-0820
	10-1/4"	28	Framing	18°	0.102"	5/8", ◆	1	48-40-1038
FINE FINISH	5-3/8"	36	Fine Finish	15°	0.063"	10 mm	1	48-40-0524
	6-1/2"	40	Fine Finish	15°	0.063"	5/8", ◆	1	48-40-0622
	7-1/4"	40	Fine Finish	15°	0.063"	5/8", ◆	1	48-40-0726
	7-1/4"	60	Ultra Fine Finish	15°	0.063"	5/8", ◆	1	48-40-0730
	8-1/4"	40	Fine Finish	15°	0.083"	5/8", ◆	1	48-40-0822
	8-1/2"	60	Fine Finish	15°	0.094"	5/8"	1	48-40-0826
	10"	60	Fine Finish	12°	0.094"	5/8"	1	48-40-1028
	10"	80	Ultra Fine Finish	12°	0.094"	5/8"	1	48-40-1032
	10-1/4"	40	Fine Finish	12°	0.102"	5/8", ◆	1	48-40-1040
	12"	80	Fine Finish	12°	0.118"	1"	1	48-40-1224
	12"	100	Ultra Fine Finish	12°	0.118"	1"	1	48-40-1228
GENERAL PURPOSE	8-1/2"	40	General Purpose	15°	0.094"	5/8"	1	48-40-0824
	10"	24	Ripping	22°	0.094"	5/8"	1	48-40-1020
	10"	40	General Purpose	15°	0.094"	5/8"	1	48-40-1024
	10"	50	Combination	12°	0.094"	5/8"	1	48-40-1026
	12"	44	General Purpose	15°	0.118"	1"	1	48-40-1220
	12"	60	Combination	12°	0.118"	1"	1	48-40-1222
MULTI-PACKS	6-1/2"	24	Framing	18°	0.063"	5/8", ◆	10	48-41-0620
	7-1/4"	24	Framing	18°	0.063"	5/8", ◆	10	48-41-0720
	7-1/4"	24	Framing	18°	0.063"	◆	10	48-41-0723
	7-1/4"	40	Fine Finish	15°	0.063"	5/8", ◆	10	48-41-0726
	7-1/4"	60	Ultra Fine Finish	15°	0.063"	5/8", ◆	10	48-41-0730
	10"	40/60	General Purpose/Fine Finish	15°/12°	0.094"	5/8"	2	48-40-1036
	10"	40/60	General Purpose/Fine Finish	15°/12°	0.094"	5/8"	2	48-40-1036
	12"	44/80	General Purpose/Fine Finish	15°/12°	0.118"	1"	2	48-40-1232
	12"	44/80	General Purpose/Fine Finish	15°/12°	0.118"	1"	2	48-40-1232