



MODELS 5715K17 / 6715K17

1.5 HP SINGLE-STAGE, TWO-CYLINDER
PORTABLE ELECTRIC COMPRESSORS



MODEL 5715K17



MODEL 6715K17

ROLAIR® STANDARD FEATURES

PUMP: ROLAIR® Quality, Heavy Duty, Single Stage, Ball Bearings, Cast-Iron Twin-Cylinders, Hardened-Steel Valve Plates with Swedish Lamellar Reed Valves, Aluminum-Alloy Connecting Rods with Automotive-Style Inserts, Multi-Finned 11" Flywheel, Oil Sight Gauge and Splash Lubrication.

MOTOR: 1.5 HP 1755 RPM Open Drip-Proof
115/230 Volts, 60 Hz Ball Bearings
Overload Protected with Manual Reset
S-1 Rated for Continuous Duty

TANK ASSEMBLY: Non-Code, 9 Gallons

WHEELS: One 410/350 x 4 Flat-Free Tire - 5715K17
Two 410/350 x 4 Flat-Free Tires - 6715K17

PERFORMANCE @ 90 PSI:

Cu. Ft. Displaced - 10.1
Cu. Ft. Delivered - 7.3

DIMENSIONS:

L46" x W19" x H28" - 5715K17
L46" x W27" x H28" - 6715K17

APPROXIMATE SHIPPING WEIGHT:

174 lb. - 5715K17

STANDARD EQUIPMENT

- Industrial "Square D" Pressure Switch with Relief Valve
- Intake Filter with Silencer and Replaceable Element
- Universal Quick-Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- 12-3 Cord with Dead Front Plug
- Accessory Support Bracket
- Pressure Gauge 0-200 in 5 lb. Graduations
- 110/135 PSI Operating Pressure
- On/Off Lever
- Safety Relief Valve
- Air-Cooled Aftercooler

OPTIONAL EQUIPMENT

Constant-Speed Operation, Dual-Control Operation, Dual-Voltage Switch,
Filter-Regulator-Lubricator Sets, Fully-Pneumatic Tires



606 South Lake Street > P.O. Box 346 > Hustisford, WI 53034-0346 > 920.349.3281 > fax 920.349.3691 > www.rolair.com

